



浙江万马天屹通信线缆有限公司

Zhejiang Wanma Tianyi Communication Wire & Cable Co., Ltd.

RG6+电源线

产品描述

	材料	直径 (mm)
内导体	CCS	1.02
绝缘	PE 发泡	4.57
铝箔	Bonded APA	4.78
编织	铝镁合金丝	
内导体	CCA/CU	7*0.37
绝缘	PE	1.75
护套	PVC	6.93



电缆特性

电容量	52 pF/m	结构回波损耗 5~1000MHz	18dB Min.
速率	82%	阻抗	75 ± 3 ohms

衰减 @ 20°C

MHz	dB/100ft	dB/100m.
55	1.60	5.25
211	3.05	10.00
250	3.30	10.82
270	3.37	11.04
300	3.55	11.64
330	3.74	12.26
350	3.85	12.63
400	4.15	13.61

MHz	dB/100ft	dB/100m.
450	4.40	14.43
500	4.66	15.29
550	4.90	16.08
600	5.10	16.73
750	5.65	18.54
870	6.11	20.04
1000	6.55	21.49



Tianyi Industrial Area, Faihuyuan Town, Lin'an City, Zhejiang 311300, China

Tel: +86 571 2361 6526 Fax: +86 571 6375 1363

www.wanmatianyi.com